select the default VPC and a random subnet, and set the `AttachVolume` parameter to `yes`. Don't forget to check the box marked "I Acknowledge That AWS CloudFormation Might Create IAM Resources." After creating the stack, use the SSM Session Manager to connect to the instance.

You can see the attached EBS volumes using `lsblk`. Usually, EBS volumes can be found somewhere in the range of /dev/xvdf to /dev/xvdp. The root volume (/dev/xvda) is an exception—it's based on the AMI you choose when you launch the EC2 instance and contains everything needed to boot the instance (your OS files), as shown here:

```
$ lsblk
NAME    MAJ:MIN RM SIZE RO TYPE MOUNTPOINT
xvda    202:0    0   8G  0 disk              ①
└─xvda1 202:1    0   8G  0 part /
xvdf    202:80   0   5G  0 disk              ②
```

① The root volume, an EBS volume with a size of 8 GiB

② An additional volume, an EBS volume with a size of 5 GiB

The first time you use a newly created EBS volume, you must create a filesystem. You could also create partitions, but in this case, the volume size is only 5 GB, so you probably don't want to split it up further. Because you can create EBS volumes in any size and attach multiple volumes to your EC2 instance, partitioning a single EBS volume is uncommon. Instead, you should create volumes at the size you need (1 GB to 16 TB); if you need two separate scopes, create two volumes. In Linux, you can create a filesystem on the additional volume with the help of `mkfs`. The following example creates an XFS filesystem: