shows the baseline and bursting write throughput of an EFS filesystem in US East (N. Virginia) where the maximum bursting throughput is 3 GiBps.

Table 9.2 EFS throughput depends on the storage size.

Filesystem size	Baseline throughput	Bursting throughput	Explanation
<=20 GiB	1 MiBps	100 MiBps	Minimum baseline throughput is 1 MiBps, and minimum bursting throughput is 100 MiBps.
1 TiB	50 MiBps	100 MiBps	The bursting throughput starts to grow with filesystems larger than 1 TiB.
30 TiB	1500 MiBps	3000 MiBps	The bursting throughput hits the maximum for filesystems in US East (N. Virginia).
>=60 TiB	3000 MiBps	3000 MiBps	Both the baseline and bursting throughput hit the maximum for filesystems in US East (N. Virginia).

As long as you are consuming less than the baseline throughput, the filesystem accumulates burst credits. For every TiB of storage, your filesystem accrues credits of 50 MiB per second. For example, a filesystem with 500 GiB accumulates burst credits for accessing 2160 GiB within 24 hours. That's bursting at the maximum of 100 MiBps for 6 hours.

WARNING EFS does not support more than 500 MiBps per client, which means an EC2 instance cannot transfer more than 500 MiBps to an EFS filesystem.