for only 150 MiBps, because 50 MiBps would be the baseline performance of a filesystem in Bursting Throughput mode.

The following code snippet shows how to provision throughput using CloudFormation. Use the efs-provisioned.yaml template to update your `efs` CloudFormation stack:

```
$ aws cloudformation update-stack --stack-name efs \
➥ --template-url https:/ /s3.amazonaws.com/awsinaction-code3/\
➥ chapter09/efs-provisioned.yaml --capabilities CAPABILITY_IAM
```

The next listing contains two differences to the template you used in the previous example: the `ThroughputMode` is set to `provisioned` instead of `bursting`, and the `ProvisionedThroughputInMibps` sets the provisioned throughput to 1 MiBps, which is free, because this is the baseline throughput of a filesystem with bursting throughput.

## Listing 9.8 EFS filesystem with provisioned throughput

```
FileSystem:
  Type: 'AWS::EFS::FileSystem'
  Properties:
    Encrypted: true
    ThroughputMode: provisioned          ①
    ProvisionedThroughputInMibps: 1      ②
    PerformanceMode: generalPurpose
    FileSystemPolicy:
      Version: '2012-10-17'
      Statement:
      - Effect: 'Deny'
        Action: '*'
        Principal:
          AWS: '*'
        Condition:
          Bool:
            'aws:SecureTransport': 'false'
```

① Sets the throughput mode from bursting to provisioned

② Configures the provisioned throughput in MiBps. 1 MiBps is free, even for empty filesystems.