```
            Value: !Ref FileSystem
          Period: 60
          Stat: Sum
          Unit: 'Bytes/Second'
        ReturnData: false
      - Expression: '(m1/1048576)/PERIOD(m1)'      ⑤
        Id: e1                                     ⑥
        Label: e1
        ReturnData: false
      - Expression: 'm2/1048576'                   ⑦
        Id: e2
        Label: e2
        ReturnData: false
      - Expression: '((e1)*100)/(e2)'              ⑧
        Id: e3
        Label: 'Throughput utilization (%)'
        ReturnData: true                           ⑨
    EvaluationPeriods: 10
    DatapointsToAlarm: 6
    ComparisonOperator: GreaterThanThreshold       ⑩
    Threshold: 80
```

① Uses metric math to combine multiple metrics

② Assigns the ID m1 to the first metric

③ The first metric taken into consideration is the MeteredIOBytes metric, which contains the current utilization.

④ The second metric is the PermittedThroughput metric, which indicates the maximum throughput.

⑤ The first metric, m1, returns the sum of bytes transferred within 60 seconds. This expression converts this into MiBps.

⑥ Assigns the ID e1 to the metric to reference it in the following line

⑦ Converts the second metric from bytes/second into MiBps

⑧ Calculates the throughput utilization in percent

⑨ The output of the third expression is the only metric/expression returning data used for the alarm.

⑩ The alarm triggers if the throughput utilization is greater than ...

...80%.

If the CloudWatch alarm flips into the `ALARM` state, you might want to increase the provisioned throughput of your filesystem.