The password for the admin user of the MySQL database

References the security group for the database instance

Defines the subnets the RDS database instance will launch into

The subnet group ...

... consists of subnet A and B, so RDS will distribute database instances among those subnets.

See if the CloudFormation stack named `wordpress` has reached the state `CREATE _COMPLETE` with the following command:

```
$ aws cloudformation describe-stacks --stack-name wordpress
```

Search for `StackStatus` in the output, and check whether the status is `CREATE_ COMPLETE`. If not, you need to wait a few minutes longer (it can take up to 15 minutes to create the stack) and rerun the command. If the status is `CREATE_COMPLETE`, you'll find the key `OutputKey` in the output section. The corresponding `OutputValue` contains the URL for the WordPress blogging platform. The following listing shows the output in detail. Open this URL in your browser; you'll find a running WordPress setup.

Listing 10.2 Checking the state of the CloudFormation stack

```
$ aws cloudformation describe-stacks --stack-name wordpress
{
  "Stacks": [{
    "StackId": "[...]",
    "Description": "AWS in Action: chapter 10",
    "Parameters": [...],
    "Tags": [],
    "Outputs": [
        {
            "Description": "WordPress URL",
            "OutputKey": "URL",
            "OutputValue": "http://[...].us-east-1.elb.amazonaws.com"  ①
        }
    ],
    "CreationTime": "2017-10-19T07:12:28.694Z",
    "StackName": "wordpress",
```