The following command changes the time frame for automated backups to 05:00–06:00 UTC and the retention period to three days. Use the terminal on your local machine to execute it:

```
$ aws cloudformation update-stack --stack-name wordpress --template-url \
➥ https:/ /s3.amazonaws.com/awsinaction-code3/chapter10/\
➥ template-snapshot.yaml \
➥ --parameters ParameterKey=WordpressAdminPassword,UsePreviousValue=true \
➥ --capabilities CAPABILITY_IAM
```

The RDS database will be modified based on a slightly modified CloudFormation template, as shown in the following listing.

Listing 10.3 Modifying an RDS database's snapshot time frame and retention time

```
Database:
  Type: 'AWS::RDS::DBInstance'
  DeletionPolicy: Delete
  Properties:
    AllocatedStorage: 5
    BackupRetentionPeriod: 3                ①
    PreferredBackupWindow: '05:00-06:00'    ②
    DBInstanceClass: 'db.t2.micro'
    DBName: wordpress
    Engine: MySQL
    MasterUsername: wordpress
    MasterUserPassword: wordpress
    VPCSecurityGroups:
    - !Sub ${DatabaseSecurityGroup.GroupId}
    DBSubnetGroupName: !Ref DBSubnetGroup
  DependsOn: VPCGatewayAttachment
```

① Keeps snapshots for three days

② Creates snapshots automatically between 05:00 and 06:00 UTC

If you want to disable automated snapshots, you need to set the retention period to `0`. As usual, you can configure automated backups using CloudFormation templates, the Management Console, or SDKs. Keep in mind that automated snapshots are deleted when the