```
$ aws cloudformation describe-stack-resource \
➥ --stack-name wordpress --logical-resource-id DBSubnetGroup \
➥ --query "StackResourceDetail.PhysicalResourceId" --output text
```

You're now ready to create a new database based on the manual snapshot you created at the beginning of this section. Execute the following command, replacing `$SubnetGroup` with the output of the previous command:

```
$ aws rds restore-db-instance-from-db-snapshot \
➥ --db-instance-identifier awsinaction-db-restore \
➥ --db-snapshot-identifier wordpress-manual-snapshot \
➥ --db-subnet-group-name $SubnetGroup
```

You might get an "DBSnapshot must have state available but actually has creating" error if your snapshot has not been created yet. In this case, retry the command after five minutes.

A new database named awsinaction-db-restore is created based on the manual snapshot. In theory, after the database is created, you could switch the WordPress application to the new endpoint by modifying the /var/www/html/wp-config.php file on both virtual machines.

If you're using automated snapshots, you can also restore your database from a specified moment, because RDS keeps the database's change logs. This allows you to jump back to any point in time from the backup retention period to the last five minutes.

Execute the following command, replacing `$DBInstanceIdentifier` with the output of the earlier `describe-db-instances` command, `$SubnetGroup` with the output of the earlier `describe-stack-resource` command, and `$Time` with a UTC timestamp from five minutes ago (e.g., `2022-03-11T09:30:00Z`):