```
➥ --parameters ParameterKey=WordpressAdminPassword,UsePreviousValue=true \
➥ --capabilities CAPABILITY_IAM
```

The RDS database is updated based on a slightly modified CloudFormation template as shown in the next listing.

### Listing 10.7 Modifying the RDS database by enabling high availability

```
Database:
  Type: 'AWS::RDS::DBInstance'
  DeletionPolicy: Delete
  Properties:
    AllocatedStorage: 5
    BackupRetentionPeriod: 3
    PreferredBackupWindow: '05:00-06:00'
    DBInstanceClass: 'db.t2.micro'
    DBName: wordpress
    Engine: MySQL
    MasterUsername: wordpress
    MasterUserPassword: wordpress
    VPCSecurityGroups:
    - !Sub ${DatabaseSecurityGroup.GroupId}
    DBSubnetGroupName: !Ref DBSubnetGroup
    MultiAZ: true                          ①
  DependsOn: VPCGatewayAttachment
```

① Enables high-availability deployment for the RDS database

It will take several minutes for the database to be deployed in HA mode. There is nothing more you need to do—the database is now highly available.

## What is Multi-AZ?

Each AWS region is split into multiple independent data centers, which are also called availability zones. We introduced the concept of availability zones in chapters 4 and 5, but skipped one aspect of HA deployment that is used only for RDS: the primary and