Where is the template located?

You can find the template on GitHub. Download a snapshot of the repository at https://github.com/AWSinAction/code3/archive/main.zip. The file we're talking about is located at chapter11/memorydb-minimal.yaml. On S3, the same file is located at http://s3.amazonaws.com/awsinaction-code3/chapter11/memorydb-minimal.yaml.

We are reusing the gaming example from section 11.1. Hopefully, your CloudFormation stack `memorydb-minimal` reached status `CREATE_COMPLETE` already. If so, open the Outputs tab and copy the EC2 instance ID as well as the cache address. Next, use the Session Manager to connect to the EC2 instance. Afterward, use the steps you used previously in section 11.1 to play with Redis. Make sure to replace `$CacheAddress` with the value from the CloudFormation outputs:

```
$ sudo amazon-linux-extras install -y redis6      ①
$ redis-cli -h $CacheAddress                      ②
> SET session:gamer1 online EX 15                 ③
OK
> GET session:gamer1                              ④
"online"
> GET session:gamer1                              ⑤
(nil)                                             ⑥
> ZADD highscore 100 "gamer1"                     ⑦
(integer) 1
> ZADD highscore 50 "gamer2"                      ⑧
(integer) 1
> ZADD highscore 150 "gamer3"                     ⑨
(integer) 1
> ZADD highscore 5 "gamer4"                       ⑩
(integer) 1
> ZRANGE highscore -3 -1 WITHSCORES
1) "gamer2"
2) "50"
3) "gamer1"
4) "100"
5) "gamer3"
6) "150"
> quit
```

① Installs the Redis CLI

② Connects to the Redis cluster node. Don't forget to replace $CacheAddress with the output from the CloudFormation stack.

③ Stores a session for user gamer1 with a time-to-live of 15 seconds