```
➥ --key-schema AttributeName=uid,KeyType=HASH \                    ③
➥ --provisioned-throughput ReadCapacityUnits=5,WriteCapacityUnits=5    ④
```

① Prefixing tables with the name of your application will prevent name clashes in the future.

② Items must at least have one attribute uid of type string.

③ The partition key (type HASH) uses the uid attribute.

④ You'll learn about this in section 12.11.

Creating a table takes some time. Wait until the status changes to `ACTIVE`. You can check the status of a table as follows.

Listing 12.2 Checking the status of the DynamoDB table

```
$ aws dynamodb describe-table --table-name todo-user     ①
{
  "Table": {
    "AttributeDefinitions": [                            ②
      {
        "AttributeName": "uid",
        "AttributeType": "S"
      }
    ],
    "TableName": "todo-user",
    "KeySchema": [                                       ③
      {
        "AttributeName": "uid",
        "KeyType": "HASH"
      }
    ],
    "TableStatus": "ACTIVE",                             ④
    "CreationDateTime": "2022-01-24T16:00:29.105000+01:00",
    "ProvisionedThroughput": {
      "NumberOfDecreasesToday": 0,
      "ReadCapacityUnits": 5,
      "WriteCapacityUnits": 5
    },
    "TableSizeBytes": 0,
    "ItemCount": 0,
    "TableArn": "arn:aws:dynamodb:us-east-1:111111111111:table/todo-user",
    "TableId": "0697ea25-5901-421c-af29-8288a024392a"
  }
}
```

① The CLI command to check the table status