```
{
    "CapacityUnits": 1.0,                                    ④
    "TableName": "todo-user"
}
```

① Tells DynamoDB to return the used capacity units

② getItem requires 0.5 capacity units.

③ A consistent read ...

④ ... needs twice as many capacity units.

More abstract rules for throughput consumption follow:

- An eventually consistent read takes half the capacity of a strongly consistent read.
- A strongly consistent `getItem` requires one read capacity unit if the item isn't larger than 4 KB. If the item is larger than 4 KB, you need additional read capacity units. You can calculate the required read capacity units using `roundUP(itemSize / 4)`.
- A strongly consistent `query` requires one read capacity unit per 4 KB of item size. This means if your query returns 10 items, and each item is 2 KB, the item size is 20 KB and you need five read units. This is in contrast to 10 `getItem` operations, for which you would need 10 read capacity units.
- A write operation needs one write capacity unit per 1 KB of item size. If your item is larger than 1 KB, you can calculate the required write capacity units using `roundUP(itemSize)`.

If capacity units aren't your favorite unit, you can use the AWS Pricing Calculator at https://calculator.aws to calculate your capacity needs by providing details of your read and write workload.

The provision throughput of a table or a global secondary index is defined in seconds. If you provision five read capacity units per