- The public and private IP addresses of the Jenkins server change after a new virtual machine is started for recovery. The Jenkins server is no longer available under the same endpoint.

You'll learn how to solve these problems in the next part of the chapter.



Cleaning up

It's time to clean up to avoid unwanted costs. Execute the following command to delete all resources corresponding to the Jenkins setup:

```
$ aws cloudformation delete-stack --stack-name jenkins-multiaz
$ aws cloudformation wait stack-delete-complete \
➥ --stack-name jenkins-multiaz                    ①
```

① Waits until the stack is deleted

13.2.3 Pitfall: Recovering network-attached storage

The EBS service offers network-attached storage for virtual machines. Remember that EC2 instances are linked to a subnet, and the subnet is linked to an availability zone. EBS volumes are also located only in a single availability zone. If your virtual machine is started in another availability zone because of an outage, the EBS volume cannot be accessed from the other availability zones. Let's say your Jenkins data is stored on an EBS volume in availability zone `us-east-1a`. As long as you have an EC2 instance running in the same availability zone, you can attach the EBS volume. If this availability zone becomes unavailable and you start a new EC2 instance in availability zone `us-east-1b`, however, you can't access that EBS volume in `us-east-1a`, which means that you can't recover Jenkins because you don't have access to the data. See figure 13.5.

Don't mix availability and durability guarantees