```
$ aws cloudformation describe-stacks --stack-name jenkins-multiaz-efs-eip \
➥ --query "Stacks[0].Outputs"
```

You can now test whether the recovery of the virtual machine works as expected. To do so, you'll need to know the instance ID of the running virtual machine. Run the following command to get this information:

```
$ aws ec2 describe-instances --filters "Name=tag:Name,\
➥ Values=jenkins-multiaz-efs-eip" "Name=instance-state-code,Values=16" \
➥ --query "Reservations[0].Instances[0].InstanceId" --output text
```

Execute the following command to terminate the virtual machine and test the recovery process triggered by autoscaling. Replace `$InstanceId` with the instance from the output of the previous command:

```
$ aws ec2 terminate-instances --instance-ids $InstanceId
```

Wait a few minutes for your virtual machine to recover. Because you're using an Elastic IP assigned to the new virtual machine on bootstrap, you can open the same URL in your browser, as you did before the termination of the old instance.



Cleaning up

It's time to clean up to avoid unwanted costs. Execute the following command to delete all resources corresponding to the Jenkins setup:

```
$ aws cloudformation delete-stack --stack-name jenkins-multiaz-efs-eip
$ aws cloudformation wait stack-delete-complete \
➥ --stack-name jenkins-multiaz-efs-eip            ①
```

① Waits until the stack is deleted

Now the public IP address of your virtual machine running Jenkins won't change, even if the running virtual machine needs to be replaced by another virtual machine in another availability zone.

Last but not least, we want to come back to the concept of an availability zone and dive into some of the details.