```
      Type: forward
    LoadBalancerArn: !Ref LoadBalancer
    Port: 80                                    ②
    Protocol: HTTP
TargetGroup:
  Type: 'AWS::ElasticLoadBalancingV2::TargetGroup'
  Properties:
    HealthCheckIntervalSeconds: 10              ③
    HealthCheckPath: '/index.xhtml'             ④
    HealthCheckProtocol: HTTP
    HealthCheckTimeoutSeconds: 5
    HealthyThresholdCount: 3
    UnhealthyThresholdCount: 2
    Matcher:
      HttpCode: '200-299'                       ⑤
    Port: 80                                    ⑥
    Protocol: HTTP
    VpcId: !Ref VPC
```

① The load balancer forwards all requests to the default target group.

② The load balancer listens on port 80 for HTTP requests.

③ Every 10 seconds ...

④ ... HTTP requests are made to /index.xhtml.

⑤ If HTTP status code is 2XX, the backend is considered healthy.

⑥ The web server on the EC2 instances listens on port 80.

Shown in the third listing is the missing part: the targets. In our example, we are using an Auto Scaling group to launch EC2 instances. The Auto Scaling group registers the virtual machine at the target group.

Listing 14.3 Creating a load balancer and connecting it to an Auto Scaling group C

```
LaunchTemplate:
  Type: 'AWS::EC2::LaunchTemplate'
  # [...]
  Properties:
    LaunchTemplateData:
      IamInstanceProfile:
        Name: !Ref InstanceProfile
      ImageId: !FindInMap [RegionMap, !Ref 'AWS::Region', AMI]
```