```
const sqs = new AWS.SQS();
const s3 = new AWS.S3();

async function receive() {
  const result = await sqs.receiveMessage({    ①
    QueueUrl: config.QueueUrl,
    MaxNumberOfMessages: 1,                    ②
    VisibilityTimeout: 120,                    ③
    WaitTimeSeconds: 10                        ④
  }).promise();

  if (result.Messages) {                       ⑤
    return result.Messages[0]                  ⑥
  } else {
    return null;
  }
};
```

① Invokes the receiveMessage operation on SQS

② Consumes no more than one message at once

③ Takes the message from the queue for 120 seconds

④ Long poll for 10 seconds to wait for new messages

⑤ Checks whether a message is available

⑥ Gets the one and only message

The receive step has now been implemented. The next step is to process the message. Thanks to the Node.js module `puppeteer`, it's easy to create a screenshot of a website, as demonstrated here.

Listing 14.6 worker.js: Processing a message (take screenshot and upload to S3)

```
async function process(message) {
  const body = JSON.parse(message.Body);           ①
  const browser = await puppeteer.launch();        ②
  const page = await browser.newPage();

  await page.goto(body.url);
  page.setViewport({ width: 1024, height: 768})
  const screenshot = await page.screenshot();      ③

  await s3.upload({ Uploads screenshot to S3
```