```
Resources:
  # [...]
  LaunchTemplate:
    Type: 'AWS::EC2::LaunchTemplate'
    Properties:
      # [...]
      LaunchTemplateData:
        ImageId: !Ref AMI                                          ②
        UserData:                                                  ③
          'Fn::Base64': !Sub |
            #!/bin/bash -ex
            trap '/opt/aws/bin/cfn-signal -e 1 --stack ${AWS::StackName} \
➥ --resource AutoScalingGroup --region ${AWS::Region}' ERR
            cd /opt/etherpad-lite/
            echo "
            {
              \"title\": \"Etherpad\",
              \"dbType\": \"mysql\",
              \"dbSettings\": {
                \"host\": \"${Database.Endpoint.Address}\",
                \"port\": \"3306\",
                \"database\": \"etherpad\",
                \"user\": \"etherpad\",
                \"password\": \"etherpad\"
              },
              \"exposeVersion\": true
            }
            " > settings.json                                      ④
            /opt/etherpad-lite/src/bin/fastRun.sh &                ⑤
            /opt/aws/bin/cfn-signal -e 0 --stack ${AWS::StackName} \
➥ --resource AutoScalingGroup --region ${AWS::Region}
# [...]
```

① The parameter to set the AMI

② The launch template references the AMI parameter.

③ Wait what? We are still using user data to inject a script into the boot process of the EC2 instance?

④ Yes, but only to create a settings file, which requires the database host name; this is not known when creating the AMI ...

⑤ ... and to start the Etherpad application.

There is only one important part missing: the Auto Scaling group. The following listing explains the details.