- *Elastic Network Interface (ENI)*—A network interface is bound to an AZ, so if this AZ goes down, your network interface will be unavailable as well. You can attach an ENI to another virtual machine in case of a smaller outage, however.
- *Amazon Virtual Private Cloud (VPC) subnet*—A VPC subnet is bound to an AZ, so if this AZ suffers from an outage, your subnet will not be reachable as well. Use multiple subnets in different AZs to remove the dependency on a single AZ.
- *Amazon Elastic Block Store (EBS) volume*—An EBS volume distributes data among multiple storage systems within an AZ. But if the whole AZ fails, your volume will be unavailable (you won't lose your data, though). You can create EBS snapshots from time to time so you can re-create an EBS volume in another AZ.
- *Amazon Relational Database Service (RDS) Multi-AZ instance*—When running in Multi-AZ mode, a short downtime (one minute) is expected if a problem occurs with the master instance while changing DNS records to switch to the standby instance.

The following services are *fault tolerant* by default. As a consumer of the service, you won't notice any failures:

- Elastic Load Balancing (ELB), deployed to at least two AZs
- Amazon EC2 security groups
- Amazon Virtual Private Cloud (VPC) with an ACL and a route table
- Elastic IP addresses (EIP)
- Amazon Simple Storage Service (S3)
- Amazon Elastic Block Store (EBS) snapshots
- Amazon DynamoDB