It takes quite a while to create that CloudFormation stack; that's why you should do so now. After you've created the stack, we'll look at the template. After that, the application should be ready to use.

To help you deploy Imagery, we have created a CloudFormation template located at http://s3.amazonaws.com/awsinaction-code3/chapter16/template.yaml. Create a stack based on that template. The stack output `EndpointURL` returns the URL that you can access from your browser to use Imagery. Here's how to create the stack from the terminal:

```
$ aws cloudformation create-stack --stack-name imagery \
➥ --template-url https:/ /s3.amazonaws.com/\
➥ awsinaction-code3/chapter16/template.yaml \
➥ --capabilities CAPABILITY_IAM
```

Next, let's have a look what is going on behind the scenes.

Bundling runtime and application into a machine image (AMI)

In chapter 15, we introduced the concept of immutable machines. The idea is to create an Amazon Machine Image (AMI) containing the runtime, all required libraries, and the application's code or binary. The AMI is then used to launch EC2 instances with everything preinstalled. To deliver a new version of your application, you would create a new image, launch new instances, and terminate the old instances. We used Packer by HashiCorp to build AMIs. Check out chapter 15 if you want to recap the details. All we want to show here is the configuration file we used to prebuild and share AMIs containing the Imagery worker and server with you.