```
          'awslogs-group': !Ref LogGroup
          'awslogs-stream-prefix': app
      Environment:                                          ⑥
      - Name: 'PASSWORD'
        Value: !Ref Password
      - Name: 'STORE_REGION'
        Value: !Ref 'AWS::Region'
      - Name: 'STORE_BUCKET'
        Value: !Ref Bucket
      - Name: COOKIE_SECURE
        Value: 'false'
    Cpu: 512                                                ⑦
    ExecutionRoleArn: !GetAtt 'TaskExecutionRole.Arn'       ⑧
    Family: !Ref 'AWS::StackName'
    Memory: 1024                                            ⑨
    NetworkMode: awsvpc                                     ⑩
    RequiresCompatibilities: [FARGATE]
    TaskRoleArn: !GetAtt 'TaskRole.Arn'
```

① Remember that a task definition describes one or multiple containers? In this example, there is only one container, called app.

② We will reference the container named app later.

③ The URL points to a publicly hosted container image bundling the Notea app.

④ The container starts a server on port 3000.

⑤ The log configuration tells the container to ship logs to CloudWatch, which is the default for ECS and Fargate.

⑥ The notea container expects a few environment variables for configuration. Those environment variables are configured here.

⑦ Tells Fargate to provision 0.5 vCPUs for our task

⑧ The IAM role is used by Fargate to fetch container images, ship logs, and similar tasks.

⑨ Tells Fargate to assign 1024 MB memory to our task

⑩ Fargate supports only the networking mode awsvpc, which will attach an Elastic Network Interface (ENI) to each task. You learned about the ENI in chapter 16 already.

Specifies that the task definition should be used with Fargate only

The IAM role used by the application to access S3

The task definition configures two IAM roles for the tasks. An IAM role is required to authenticate and authorize when accessing any AWS services. The IAM role defined by `ExecutionRoleArn` is not very