C++ Binary Operators are classified as:

(1) Arithmetic Operators
(2) Relational Operators
(3) Logical Operators
(4) Assignment Operators
(5) Conditional Operator

(1) Arithmetic Operators

Arithmetic operators perform simple arithmetic operations like addition, subtraction, multiplication, division etc.,

Operator	Operation	Example
+	Addition	10 + 5 = 15
-	Subtraction	10 – 5 = 5
*	Multiplication	10 * 5 = 50
/	Division	10 / 5 = 2 (Quotient of the division)
%	Modulus (To find the remainder of a division)	10 % 3 = 1(Remainder of the division)

- The above mentioned arithmetic operators are binary operators which requires minimum of two operands.

Increment and Decrement Operators

++ (Plus, Plus) Increment operator

-- (Minus, Minus) Decrement operator

An increment or decrement operator acts upon a single operand and returns a new value. Thus, these operators are unary operators. The increment operator adds 1 to its operand and the decrement operator subtracts 1 from its operand. For example,

- **x++ or ++ x** is the same as **x = x+1;**

  It adds 1 to the present value of x
- **x -- or -- x** is the same as to **x = x–1**;

  It subtracts 1 from the present value of x

The ++ or -- operators can be placed either as prefix (before) or as postfix (after) to a variable. With the prefix version, C++ performs the increment / decrement before using the operand.

(2) Relational Operators

Relational operators are used to determine the relationship between its operands. When the relational operators are applied on two operands, the result will be a Boolean value i.e 1 or 0 to represents True or False respectively. C++ provides six relational operators. They are,

Operator	Operation	Example
>	Greater than	a > b
<	Less than	a < b
>=	Greater than or equal to	a >= b
<=	Less than or equal to	a <= b
==	Equal to	a == b
!=	Not equal	a != b

- In the above examples, the operand *a* is compared with *b* and depending on the relation, the result will be either 1 or 0. i.e., 1 for true, 0 for false.
- All six relational operators are binary operators.

(3)Logical Operators

A logical operator is used to evaluate logical and relational expressions. The logical operators act upon the operands that are themselves called as logical expressions. C++ provides three logical operators.

Table 9.3 Logical Operators

Operator	Operation	Description
&&	AND	The logical AND combines two different relational expressions in to one. It returns 1 (True), if both expression are true, otherwise it returns 0 (false).

Chapter 9 Page 115-151.indd 120 3/24/2020 9:21:03 AM