Output-1

Enter a Character: 3
The Return Value of isdigit(ch) is :1

Output-2

Enter a Character: A
The Return Value of isdigit(ch) is :0

***Return 0; (Not Compulsory in latest compilers)**

11.4.2.4. islower()

This function is used to check whether a character is in lower case (small letter) or not. This functions will return a non-zero value, if the given character is a lower case alphabet, and 0 otherwise.

General Form:

islower(char c)

After executing the following statements, the value of the variable **n** will be **1** since the given character is in lower case.

```
char ch = 'n';
int n = islower(ch);
```

But the statement given below will assign 0 to the variable n, since the given character is an uppercase alphabet.

```
int n = islower('P');
```

11.4.2.5. isupper()

This function is used to check the given character is uppercase. This function will return 1 if true otherwise 0.

General Form:

isupper(char c)

For the following examples value **1** will be assigned to **n** and **0** for m.

```
int n=isupper('A');
int m=isupper('a');
```

11.4.2.6. toupper()

This function is used to convert the given character into its uppercase. This function will return the upper case equivalent of the given character. If the given character itself is in upper case, the output will be the same.

General Form:

char toupper(char c);

The following statement will assign the character constant **'K'** to the variable c.

```
char c = toupper('k');
```

But, the output of the statement given below will be **'B'** itself.

```
cout <<toupper('B');
```

11.4.2.7. tolower()

This function is used to convert the given character into its lowercase. This function will return the lower case equivalent of the given character. If the given character itself is in lower case, the output will be the same.

General Form:

char tolower(char c)

The following statement will assign the character constant **'k'** to the variable c.

```
char c = tolower('K');
```

But, the output of the statement given below will be **'b'** itself.

```
cout <<tolower('b');
```

11.4.3 String manipulation (string.h)

The library **string.h** (also referred as cstring) has several common functions for dealing with strings stored in array of characters. The string.h header file is to be included before using any string function.

Chapter 11 Page 180-205.indd 185 3/24/2020 9:22:03 AM