11.4.3.1 strcpy()

General Form:

strcpy(Target String, Source String)

The **strcpy()** function takes two arguments: target and source. It copies the character string pointed by the source to the memory location pointed by the target. The null terminating character **(\0)** attached to the string is also copied.

Program 11.6

```
#include <string.h>
#include <iostream>
using namespace std;
int main()
{
        char source[] = "Computer Science";
        char target[20]="target";
        cout<<"\n String in Source Before Copied :"<<source;
        cout<<"\n String in Target Before Copied :"<<target;
        strcpy(target,source);
        cout<<"\n String in Target After strcpy function Executed :"<<target;
        return 0;
}
```

Output:

```
String in Source Before Copied :Computer Science
String in Target Before Copied :target
String in Target After strcpy function Executed :Computer Science
```

11.4.3.2 strlen()

The **strlen()** takes a null terminated string as its argument and returns its length. The length does not include the null(\0) character.

General Form:

strlen(string)

Program 11.7

```
#include <string.h>
#include <iostream>
using namespace std;
int main()
{
        char source[ ] = "Computer Science";
        cout<<"\n Given String is "<<source<<" its Length is "<<strlen(source);
        return 0;
}
```

Output:

```
Given String is Computer Science its Length is 16
```


Chapter 11 Page 180-205.indd 186 3/24/2020 9:22:03 AM