### 11.4.3.3 strcmp()

The **strcmp()** function takes two arguments: string1 and string2. It compares the contents of string1 and string2 lexicographically.

**General Form:**

**strcpy(String1, String2)**

**The strcmp() function returns a:**

- Positive value if the first differing character in string1 is greater than the corresponding character in string2. (ASCII values are compared)
- Negative value if the first differing character in string1 is less than the corresponding character in string2.
- 0 if string1 and string2 are equal.

**Program 11.8**

```
#include <string.h>
#include <iostream>
using namespace std;
int main()
{
        char string1[] = "Computer";
        char string2[] = "Science";
        int result;
        result = strcmp(string1,string2);
        if(result==0)
        {
        cout<<"String1 : "<<string1<<" and String2 : "<<string2 <<"Are Equal";
        }
        if (result<0)
        {
        cout<<"String1 :"<<string1<<" and String2 : "<<string2 <<" Are Not Equal";
        }
}
```

**Output**

String1 : Computer and String2 : Science Are Not Equal

### 11.4.3.4 strcat()

The **strcat()** function takes two arguments: target and source. This function appends copy of the character string pointed by the source to the end of string pointed by the target.



Chapter 11 Page 180-205.indd 187 3/24/2020 9:22:03 AM