Program 11.13

```
#include <iostream>
#include <math.h>
using namespace std;
int main()
{
        double x = 625, result;
        result = sqrt(x);
        cout << "sqrt("<<x<<") = "<<result;
        return 0;
}
```

Output:

```
        sqrt(625) = 25
```

11.4.4.3 sin() function

The **sin()** function takes a single argument in radians. The **sin()** function returns the value in the range of [-1, 1]. The returned value is either in double, float, or long double.

11.4.4.4 pow() function

The **pow()** function returns base raised to the power of an exponent. If any argument passed to **pow()** is long double, the return type is promoted to long double. If not, the return type is double. The **pow()** function takes two arguments:

- **base** - the base value
- **exponent** - exponent of the base

Program 11.14

```
#include <iostream>
#include <math.h>
using namespace std;
int main ()
{
        double base, exponent, result;
        base = 5;
        exponent = 4;
        result = pow(base, exponent);
        cout << "pow("<<base << "^" << exponent << ") = " << result;
        double x = 25;;
        result = sin(x);
        cout << "\nsin("<<x<<")= "<<result;
        return 0;
}
```

Output:

```
        pow(5^4) = 625
        sin(25)= -0.132352
```


Chapter 11 Page 180-205.indd 190 3/24/2020 9:22:03 AM