An **inline** function looks like normal function in the source file but inserts the function's code directly into the calling program. To make a function inline, one has to insert the keyword **inline** in the function header.

Syntax :

inline returntype functionname(datatype parameter 1, … datatype parameter n)

Advantages of inline functions:

- Inline functions execute faster but requires more memory space.
- Reduce the complexity of using STACKS.

Program 11.19

```
#include <iostream>
using namespace std;
inline int add (int a , int b)
{
        int c=a+b;
        return(c);
}
int main ()
{
        int x,y,z;
        cout<<"\nEnter the First Number :";
        cin>>x;
        cout<<"\nEnter the second Number     :";
        cin>>y;
        z=add(x,y);
        cout << "\n sum of "<<x<<"+"<<y<<"="<<z;
        return 0;
}
```

Output:

```
Enter the First Number :10
Enter the second Number     :20
sum of 10+20=30
```

Though the above program is written in the normal function definition format during compilation the function code **a+b** will be directly inserted in the calling statement i.e. **z=add(x,y);** this makes the calling statement to change as **z = a+b;**

11.7 Different forms of User-defined Function declarations

11.7.1 A Function without return value and without parameter

The following program is an example for a function with no return and no arguments passed .

Chapter 11 Page 180-205.indd 196 3/24/2020 9:22:04 AM