In the above program, statement **S1** displays the value of the 3rd element (subscript index 2). **S2** will display the value of the 5th element (ie. Subscript value is 3+1 = 4). In the same way statement **S3** will display the value of the 4th element.

C++ program to inputs 10 values and count the number of odd and even numbers

```
#include <iostream>
using namespace std;
int main()
{
        int num[10], even=0, odd=0;
        for (int i=0; i<10; i++)
        {
                cout<< "\n Enter Number " << i+1 <<"= ";
                cin>>num[i];
                if (num[i] % 2 == 0)
                 ++even;
                else
                 ++odd;
        }
        cout << "\n There are "<< even <<" Even Numbers";
        cout << "\n There are "<< odd <<" Odd Numbers";
}
```

Output:

```
Enter Number 1= 78
Enter Number 2= 51
Enter Number 3= 32
Enter Number 4= 66
Enter Number 5= 41
Enter Number 6= 68
Enter Number 7= 27
Enter Number 8= 65
Enter Number 9= 28
Enter Number 10= 94
There are 6 Even Numbers
There are 4 Odd Numbers
```

(HOTS : Rewrite the above program using the conditional operator instead of if)

Searching in a one dimensional array:

Searching is a process of finding a particular value present in a given set of numbers. The linear search or sequential search compares each element of the list with the value that has to be searched until all the elements in the array have been traversed and compared.

Chapter 12 Page 206-227.indd 210 3/24/2020 9:22:23 AM