```
        if(flag==1)
                cout<<"\n The String is palindrome";
        else
                cout<<"\n The String is not palindrome";
        return 0;
}
```

Output:


```
        Enter a string : madam
        The String is palindrome
```

12.3 Two-dimensional array

Two-dimensional (2D) arrays are collection of similar elements where the elements are stored in certain number of rows and columns. An example m × n matrix where m denotes the number of rows and n denotes the number of columns is shown in Figure12.4

int arr[3][3];

2D array conceptual memory representation



The array arr can be coneptually viewed in matrix form with 3 rows and 3 coloumns. The point to be noted here is since the subscript starts with 0 arr [0][0] represents the first element.

Figure 12.4

12.3.1 Declaration of 2-D array

The declaration of a 2-D array is

data-type array_name[row-size][col-size];

In the above declaration, data-type refers to any valid C++ data-type, array_name refers to the name of the 2-D array, row-size refers to the number of rows and col-size refers to the number of columns in the 2-D array.

For example

```
int A[3][4];
```

In the above example, A is a 2-D array, 3 denotes the number of rows and 4 denotes the number of columns. This array can hold a maximum of 12 elements.

Note

Array size must be an unsigned integer value which is greater than 0. In arrays, column size is compulsory but row size is optional.

Chapter 12 Page 206-227.indd 214 3/24/2020 9:22:23 AM