(Anonymous Structure Vs Named Structure)
A structure without a name/tag is called anonymous structure.

```
struct
{
long rollno;
        int age;
        float weight;
} student;
```

The student can be referred as reference name to the above structure and the elements can be accessed like student.rollno, student.age and student.weight .

12.5.4 Initializing structure elements

Values can be assigned to structure elements similar to assigning values to variables.

Example

```
balu.rollno= "702016";
balu.age= 18;
balu.weight= 48.5;
```

Also, values can be assigned directly as similar to assigning values to Arrays.

```
balu={702016, 18, 48.5};
```

12.5.5 Structure Assignment

Structures can be assigned directly instead of assigning the values of elements individually.

Example

If Mahesh and Praveen are same age and same height and weight then the values of Mahesh can be copied to Praveen

```
struct Student
{
        int  age;
        float height, weight;
}mahesh;
```

Structure assignment is possible only if both structure variables/ objects are same type.

The age of Mahesh is 17 and the height and weights are 164.5 and 52.5 respectively.The following statement will perform the assignment.

```
mahesh = {17, 164.5, 52.5};
praveen =mahesh;
```

will assign the same age, height and weight to Praveen.

Chapter 12 Page 206-227.indd 221 3/24/2020 9:22:24 AM