Output

```
Constructor without parameters..
 Parameterized constructor...
 Copy Constructor ...
Enter data ...  20 30
 Object a :
 The numbers are..20    30
 The sum of the numbers are.. 50
 Object b :
 The numbers are..10    20
 The sum of the numbers are.. 30
 Object c..
 The numbers are..10    20
 The sum of the numbers are.. 30
```

Note

Since, there are multiple constructors present, argument to the constructor should also be passed while creating an object.

15.4 Operator overloading

The term Operator overloading, refers to giving additional functionality to the normal C++ operators like +,++,-,—,+=,-=,*.<,>. It is also a type of polymorphism in which an operator is overloaded to give user defined meaning to it .

For example '+' operator can be overloaded to perform addition on various data types, like for Integer, String(concatenation) etc.

Almost all operators can be overloaded in C++. However there are few operator which can not be overloaded. Operator that are not overloaded are follows

- Scope operator (**::**)
- Sizeof
- Member selector (**.**)
- Member pointer selector (*)
- Ternary operator (**?:**)

Operator Overloading Syntax

Keyword **Operator to be overloaded**

```
ReturnType classname :: Operator Operator Symbol (argument list)
{        \\ Function body }
```


Chapter 15 Page 249-259.indd 253 3/24/2020 9:23:24 AM