Points to Remember

- In C++, polymorphism is achieved through function overloading and operator overloading.
- The term overloading means a name having two or more distinct meanings.
- Overloaded function' refers to a function having more than one distinct meaning.
- Overloaded functions have same name but different signatures (Number of argument and type of argument)
- A function's argument list is known as a function signature
- Two function cannot be overloaded when the only difference is that one takes a reference parameter and the other takes a normal, call-by-value parameter.
- Ordinary functions as well member functions can be overloaded
- A class can have overloaded constructors where as destructor function cannot be overloaded.
- The mechanism of giving special meaning to an operator is known as operator overloading.
- Operator overloading provides new definitions for most of the C++ operators.
- Even user defined types (objects) can be overloaded.
- The definition of the overloaded operator is given using the keyword 'operator' followed by an operator symbol.
- We can overload all the C++ operators except the following:
- Scope resolution operator (::), sizeof (), Conditional operator (?:), Member selection(.) and Member pointer selector (*) operator

Evaluation

FDAP72

SECTION – A

Choose the correct answer

1. Which of the following refers to a function having more than one distinct meaning?

   (A) Function Overloading (B) Member overloading

   (C) Operator overloading (D) Operations overloading

2. Which of the following reduces the number of comparisons in a program ?

   (A) Operator overloading (B) Operations overloading

   (C) Function Overloading (D) Member overloading

3.
```
void dispchar(char ch='$',int size=10)
    {
        for(int i=1;i<=size;i++)
        cout<<ch;
    }
```


Chapter 15 Page 249-259.indd 256 3/24/2020 9:23:24 AM