```
{cout<<"Vote of thanks"<<endl; } };
int main()
{       Seminar s1,s2(2),s3(s2);
        s1.Lecture();
        return 0;
}
```

4. Answer the questions based on the following program

```
#include<iostream>
#include<string.h>
using namespace std;
class comp {
public:
char s[10];
void getstring(char str[10])
  { strcpy(s,str);    }
void operator==(comp);
};
void comp::operator==(comp ob)
{ if(strcmp(s,ob.s)==0)
 cout<<"\nStrings are Equal";
else
 cout<<"\nStrings are not Equal"; }
int main()
{ comp ob, ob1;
char string1[10], string2[10];
cout<<"Enter First String:";
cin>>string1;
ob.getstring(string1);
cout<<"\nEnter Second String:";
cin>>string2;
ob1.getstring(string2);
ob==ob1;
return 0; }
```

(i) Mention the objects which will have the scope till the end of the program.

(ii) Name the object which gets destroyed in between the program

(iii) Name the operator which is over loaded and write the statement that invokes it.

(iv) Write out the prototype of the overloaded member function

(v) What types of operands are used for the overloaded operator?

(vi) Which constructor will get executed in the above program? Write the output of the program

CASE STUDY

Suppose you have a Kitty Bank with an initial amount of Rs500 and you have to add some more amount to it. Create a class 'Deposit' with a data member named 'amount' with an initial value of Rs500. Now make three constructors of this class as follows:

1. without any parameter - no amount will be added to the Kitty Bank
2. having a parameter which is the amount that will be added to the Kitty Bank
3. whenever amount is added an additional equal amount will be deposited automatically

Create an object of the 'Deposit' and display the final amount in the Kitty Bank.

Reference:

1. Object Oriented Programming with C++ (4th Edition), Dr. E. Balagurusamy, Mc.Graw Hills.
2. The Complete Reference C++ (Forth Edition), Herbert Schildt. Mc.Graw Hills.
3. The C++ Programming Language,BjarneStroustrup

Chapter 15 Page 249-259.indd 259 3/24/2020 9:23:24 AM