3.3 Give the sequence of Constructor/ Destructor Invocation when object of class Result is created.

3.4. Name the base class(/es) and derived class (/es).

3.5 Give number of bytes to be occupied by the object of the following class:
(a) Personal (b) Marks
(c) Result

3.6. Write the names of data members accessible from the object of class Result.

3.7. Write the names of all member functions accessible from the object of class Result.

3.8 Write the names of all members accessible from member functionsof class Result.

4. Write the output of the following program

```
#include<iostream>
using namespace std;
class A
{       protected:
      int x;
      public:
      void show()
      {cout<<"x = "<<x<<endl;}
      A()
      { cout<<endl<<" I am class A "<<endl;}
      ~A()
      { cout<<endl<<" Bye ";} };
class B : public A
{protected:
 int y;
 public:
 B(int x1, int y1)
 { x = x1;
  y = y1;       }
B()
{   cout<<endl<<" I am class B "<<endl; }
~B()
{   cout<<endl<<" Bye "; }
void show()
{ cout<<"x = "<<x<<endl;
  cout<<"y = "<<y<<endl;    } };
int main()
{A objA;
B objB(30, 20);
objB.show();
return 0;  }
```

5. Debug the following program

```
%include(iostream.h)
#include<conio.h>
class A()
{ public;
int a1,a2:a3;
void getdata[]
{       a1=15;  a2=13; a3=13; }         }
class B:: public A()
{       PUBLIC
        voidfunc()
        { int b1:b2:b3;
          A::getdata[];
          b1=a1;
          b2=a2;
          a3=a3;
          cout<<b1<<'\t'<<b2<<'t\'<<b3; }
void main()
{       B der;
        der1:func(); }
```

CASE STUDY

Write a class for a class Stock

Each Stock has a data member which holds the net price, and a constructor which sets this price. Each Stock has a method get_Price(), which calculates and returns the gross price (the gross price includes VAT at 21%)

Reference:

Object Oriented Programming with C++ (4th Edition), Dr. E. Balagurusamy, Mc.Graw Hills.

Chapter 16 Page 260-274.indd 274 3/24/2020 9:23:56 AM