10.3 HTML Attributes

Attributes are special words used inside a tag to specify additional information to a tag. Attributes should be placed within the opening tag. Most of the tags support specialized attributes and there are also a few global elements that can be used with any tag. Global elements are common to all HTML elements; they can be used on all elements.

10.3.1 Attributes for Structural Tags

1. Attributes of <html> tag

The **<html>** tag is used to specify the beginning and closing of an HTML document. This tag does not have any effect on appearance of document. This is only used to make browsers and other programs, known that this is an HTML document.

<html> tag has two attributes viz. **dir** and **lang** to specify the **text direction** and **language setting** respectively.

attribute	Value to be set to attribute	Description
dir	ltr (align left-to-right) rtl (align right-to-left)	dir attribute specifies the direction of the text to be aligned within the entire document. It is global attribute. • ltr is the default value • rtl is used for Arabian languages.
lang	Predefined language code English – en Tamil – ta Telugu – te	lang attribute specify the language used with in the document. Predefined language code will be used for this purpose. Malayalam – ml; Kannada – kn; Hindi – hi; French – fr; German – de;

2. Attributes of <body> tag

The <body> tag defines the document's body. The contents of an HTML page reside within the <body> tag. <body> tag contains several attributes.

(i) Background Colour: bgcolor = color

` By default all the browsers display the text on white background. However, the background color of the browser can be changed by using bgcolor tag.

The tag to change background colour:

<body bgcolor = color_name/color_code>

Chapter 10 Pages 28-53.indd 224 3/20/2020 11:39:10 AM