Illustration: 11.6 Usage of <del> and <ins>

```
<html>
<head>
<title> Inserting and Deleting text </title>
</head>
<body>
                I am coming from <del> Madras</del>  <ins> Chennai </ins>
</body>
</html>
```

11.1.7 Strike through:

To display a text as wrong text, the **<s>** tag can be used to show the text as strike through style. The **<s>** and **<del>** tags are display the text in similar way. This is also a container tag. The text you specify between **<s>** and **</s>** will be display in strike through style.

11.1.8 Comparison of tags:

A few tags do the same things you have learned so far. For example, **<b>** and ****, **<i>** and **, <u>** and **<ins>** and so on. These tags may be shows the same output, but the usage of tags are varying. The following table shows the usage of this kind of tags.

Table: 11.2

Tag	Usage	Tag	Usage	Final Output
<b>	To show the text in bold	****	To show important text	Bold
<i>	To show the text as italics	****	To Call attention	Italics
<u>	To show the text as underlined	**<ins>**	To insert a text	Underline
<s>	To show the wrong text	**<del>**	To replaced or deleted text	Strike through

While writing HTML document, you should use the appropriate tags according to its usage. If you want show a text as underlined use <**u**> instead of <ins>.

11.1.9 The Center Tag

Paragraphs can be centered with Align attribute with <p> tag. But for non-paragraph text contents can be centered with tag. The tag is used to centralize a segment of text. It is a container tag. That means, what you type between and will be displayed in the center of the browser.

Chapter 11 Pages 54-92.indd 243 3/20/2020 11:42:46 AM