Illustration 12.5: An HTML code to demonstrate adding audio and video files (internal source)

```
<html>
<head>
<title> Adding Multimedi Files </title>
</head>
<body>
<img src="D:\Images\TN_Logo.png" alt="Govt. of Tamilnadu Logo" height=25% width=15%>
<marquee> Welcome to <b> The State Council of Educational Research and Traning </b>, Tamilnadu </marquee>
<embed src="D:\CS_Videos\CS_Video.mp4" width=50% height=50%> </embed>
</body>
</html>
```

12.3.1 Background music:

Music can be played in the background to a webpage, while the page is viewed. This is known as 'inline' sound or movie. The <bgsound> tag is used to attach an inline sound file in HTML. The src attribute is used to define the location of the media file. Volume attribute used to adjust volume control. The loop attribute defines the duration of play. The 'infinite' value causes the audio play as long as the page is in view.

General Format:

<bgsound src=music file name with location>

Illustration 12.6: An HTML code to demonstrate inline sound

```
<html>
<head>
<title> Inline Sound </title>
</head>
<body>
    <img src="D:\Images\TN_Logo.png" alt="Govt. of Tamilnadu Logo" height=25% width=15%>
    <marquee> Welcome to <b> The State Council of Educational Research and Training </b>, Tamilnadu </marquee>
    <bgsound src="D:\CS_Videos\Tamil Thai Vazhthu.mp3" loop=infinite>
</body>
</html>
```


Chapter 12 Pages 93-115.indd 274 3/20/2020 11:43:03 AM