CSS style declaration consists of two major parts; Selector and Declaration. The Selector refers an HTML tag in which you want to apply styles. The Declaration is a block of code contains style definition. It should be surrounded by curly braces. You can include any number of properties for each selector, and they must be separated by semicolons. The property name and its value should be separated by a colon. Each declaration should be terminated by a semicolon (;).

Example:

Selector	Declaration of properties and values
P	{ **Font-size : 16pt; color : red; font-weight : bold;** }

In the above example, the style properties are defined to **<p>** tag. Hereafter, whenever you use the <p>, the contents will be displayed with modified properties. If you want to use the above style definition as an internal style then it should be specified within **<style> …… ,</style>** block in head section. If you want store the above definition for using all your web pages, you should save the above code as a separate file with extension .css

CSS – Frequently using Text formatting Properties and Values

Table: 13.1

Formatting	Properties	Values	Example

Text Colour	Color	Predefined_Color_Name	P
			{
			color:pink;
			}
			H1
			{
			color : MediumSeaGreen;
			}

Text Alignment	Text-align	Center / Left / Right / Justify	P
			{
			Text-align : center;
			}

Font type	Font-family	Font_name	P
			{
			Font-family : “Times New Roman”;
			}

Font Style	Font-style	Normal / Italic	P
			{
			Font-family : “Times New Roman”;
			Font-style : Italic;
			}

Chapter 13 Pages 116-126.indd 288 3/20/2020 11:43:21 AM