Lexical structure specifies variable names, the delimiter characters for comments, and how one program statement is separated from the next.

- Though JavaScript is a case-sensitive language. It is good programming practice to type the command in lowercase.
- JavaScript ignores spaces that appear between tokens (identifiers, operators, punctuator, constants and keywords) in programs.
- JavaScript supports two styles of comments. Any text follow a "//" and the end of a line is treated as a single line comment and is ignored by JavaScript. Any text between the characters " /* */" is also treated as a multiline comment.
- JavaScript uses the semicolon (;) to separate statements. Many JavaScript programmers use semicolons to explicitly mark the ends of statements.
- A literal is a data value for variable that appears directly in a program.
- An identifier is simply a name. In JavaScript, identifiers are used to name variables, functions and to provide labels for certain loops in JavaScript code.
- In JavaScript certain **keywords** are used as reserved words, These words cannot used as identifiers in the programs

14.5 JavaScript Variables:

Variable is a memory location where value can be stored. Variable is a symbolic name for a value. Variables are declared with the **var** keyword in JavaScript. Every variable has a name, called identifier.

14.5.1 Basic Data types and Declaring variables:

Every variable has a data type that indicates what kind of data the variable holds. The basic data types in JavaScript are Strings, Numbers, and Booleans.

- A **string** is a list of characters, and a string literal is indicated by enclosing the characters in single or double quotes. Strings may contain a single character or multiple characters, including whitespace and special characters such as **\n** (the newline).
- **Numbers** can be integer or floating-point numerical value and numeric literals are specified in the natural way.
- **Boolean** can be any one of two values: **true** or **false**. Boolean literals are indicated by using true or false directly in the source code.

Variables are declared in JavaScript using var keyword that allocates storage space for new data and indicates to the interpreter that a new identifier is in use. Declaring a variable in JavaScript as follows:

```
var no;
var no1,no2;
```

The **var no;** statement tells the interpreter that a new variable **no** is about to be used and **var no1,no2**; tells the interpreter that **no1** and **no2** are variables.

14.5.2 Rules for naming variable

1. The first character must be a letter or an underscore (_). Number cannot be as the first

Chapter 14 Pages 127-153.indd 296 3/20/2020 11:44:35 AM