14.6 JavaScript Operators and Expressions

An operator combines the values of its operands in some way and evaluates to a new value. Operators are used for JavaScript's arithmetic expressions, comparison expressions, logical expressions, assignment expressions.

An expression is a phrase of JavaScript that a JavaScript interpreter can evaluate to produce a value. The data types are used directly as literals or within variables in combination with simple operators, such as addition, subtraction, and so on, to create an expressions. An expression is a code fragment that can be evaluated to some data type the language supports. An expression is simply one or more variables and/or constants joined by operators. An expression is evaluated and produces a result. The result of all expressions may be either an integer or floating-point value or Boolean value. There are three types of expressions as follows,

- Arithmetic expressions
- Relational expressions
- Logical expressions

14.6.1 Arithmetic Operators

JavaScript supports all the basic arithmetic operators like addition (+), subtraction (–), multiplication (*), division (/), and modulus (%, also known as the remainder operator).

Table: 14.1 – Arithmetic Operators

Arithmetic Operator	Meaning	Example	Result
+	Addition	var sum = 20 + 120	Variable sum = 140
-	Subtraction	var diff = 20 – 120	Variable diff = 100
*	Multiplication	var prod = 10 * 100	Variable prod = 1000
/	Division	var res = 100/522	Variable res = 5.22
%	Modulus operator	var rem = 100 % 522	Variable rem = 22 (remainder)

Illustration 14.3 Using Arithmetic Operators

```
<Html>
<Head>
        <Title>Demo Program – To test Arithmetic Operators in JavaScript
</Title>
</Head>
<Body>
        <script language="javascript" type="text/javascript">
```


Chapter 14 Pages 127-153.indd 299 3/20/2020 11:44:36 AM