var m = 1, n = ++m; // m and n are both 2

var m = 1, n = m++; // m is 2, n is 1

The -- operator decrements its single operand. It converts the value of the operand to a number, subtracts 1, and assigns the decremented value back to the operand. Like the ++ operator, the return value of -- depends on its position relative to the operand. When used before the operand, it decrements and returns the decremented value. When used after the operand, it decrements the operand but returns the undecremented value.

var m = 2, n = --m; // m and n are both 1

var m = 2, n = m--; // n is 2, n is 1

Illustration 14.8 Using ++ and -- Operator – both Prefix and Suffix

```
<Html>
<Head>
        <Title>Demo Program - ++ and -- Operators in JavaScript </Title>
</Head>
<Body>
        <script language="javascript" type="text/javascript">
        var number1 = 150;
        var number2 = number1++;
        document.write("<br><h4>Post Increment - number++</h4>");
        document.write("Number1 = "+number1+" Number2 = "+number2);
        document.write("<br><h4>Pre Increment - ++number</h4>");
        var number1 = 150;
        var number2 = ++number1;
        document.write("Number1 = "+number1+" Number2 = "+number2);
        var number1 = 150;
        var number2 = number1--;
        document.write("<br><h4>Post Decrement - number--</h4>");
        document.write("Number1 = "+number1+" Number2 = "+number2);
        document.write("<br><h4>Pre Decrement - --number</h4>");
        var number1 = 150;
        var number2 = --number1;
        document.write("Number1 = "+number1+" Number2 = "+number2);
</script>
</Body>
</Html>
```


Chapter 14 Pages 127-153.indd 306 3/20/2020 11:44:36 AM