Table: 16.1 Predefined functions

Function	Description	Example	Result
toUpperCase()	Used to convert given string into uppercase	x=”java” x.toUpperCase();	JAVA
toLowerCase()	Used to convert given string into lowercase	x=”JAVA” x.toLowerCase();	java
length	Used to find length of the given string	x=”JAVA” x.length();	4
parseInt()	Used to convert the given float value into an integer	parseInt(34.234);	34
parseFloat()	Used to convert the given string into a integer	parseInt(“34.23”);	34.23

16.3 User defined functions

User-defined functions allow the programmer to modularize a program. Most computer programs that solve real-world problems are much large, occupy more space in the computer memory and takes more time to execute. Hence such large programs are divided into small programs are called **modules.**

Function Definition

The format of a function definition is

```
Function function-name(parameters list)
{
    Declaration of variable
    Executable statements;        Function Body
}
```

Note:

- The function-name is any valid identifier.
  For Example: sum
- The parameter list contains one or more valid variable name.
- Parameter list contains more than one variable then comma must be there between the variable. For example: function sum(x,y)
- The function body must be enclosed by braces.

Example:

```
function sum(x,y)
    {
        var m=x+y;
        return m;
    }
```


Chapter 16 Pages 176-183.indd 332 3/20/2020 11:45:07 AM