Who are the contributors for the development of Spinning Mule?

James Hargreaves was a weaver, carpenter from Lancashire, England. He was one of three inventors responsible for mechanizing spinning. Hargreaves was the one, who improved it with spinning jenny in 1764. Later in 1769 Richard Arkwright patented the water frame and finally Samuel Crompton combined both the creations to develop the Spinning Mule.



Spinning Mule

Characteristics of Spun and Filament Yarn

	Spun Yarn	Filament Yarn
1.	Made with short fibres (e.g. : Cotton and wool)	Made using long filaments (e.g. : Silk)
2.	Protruding fibres are visible	Protruding fibers are not seen
3.	Looks dull and fuzzy	Looks smooth and lustrous
4.	Pilling is seen	Pilling is not seen
5.	Attracts dust easily	Do not Attract dust easily
6.	Gives warmthness	Gives coolness
7.	Bulky	Little bulkier
8.	Snagging easily	Snagging depends upon the type of fabric
9.	Stretch depends upon yarn twist	Stretch depends upon yarn twist
10.	Absorbs quickly	Absorbency depends on the fibres
11.	Number of twists is limited can be made	A very high or very low twist can be made
12.	Manufacturing process is difficult	It can be manufactured easily

a. Balanced Yarn

An evenly twisted yarn is called as balanced yarn and is used for making smoother fabric.

b. Unbalanced Yarn

Unevenly twisted yarns are called as unbalanced yarns and are used for making crepe and textured surface fabric.

TDD_Final_Chapter04.indd 34 21-02-2019 11.18.01 AM