8.5 CAUSES OF FAULTS AND REMEDIES OF SEWING MACHINE:

Problems faced in the sewing machine and how it can be solved are listed below:

Breaking of Thread	
Reason	**Remedies**
• Unsuitability of thread used for the fabrics.	• Suitable thread should be used for the fabrics, (For silk fabrics thin and delicate thread).
• If tension disc is too tight.	• Correct the tension.
• Using low quality thread.	• Use high quality thread.
• Rotating the wheel in anti-clock wise direction.	• Care to be taken to rotate the wheel in clock-wise direction.
• The thread cuts when the machine is sewed in thicker layers of fabric.	• Cut the broken thread, and sew again by slightly lifting the presser foot.
• Fast movement of the fabric.	• Life up the presser foot and slowly pull the fabric to its place and then stitch.
• Fixing of needle unevenly.	• Attach the needle correctly.

Breaking of Needle	
Reason	Remedies
• Using unsuitable kind of needle.	• Check and use correct needle.
• Fixing of needle at lower lever.	• Fix the needle correctly.
• If needle is blunt.	• Use a straight needle.
• If shaft is lower.	• Check the position of the needle in the needle bar.
• Pulling of the garment backward while stitching quickly.	• Raise the presser foot, lift the needle and carefully remove the garment.

Looped Stitch	
Reason	**Remedies**
• If thread is stuck in the hook of the bobbin, then loop is formed.	• Remove the stuck thread.
• If tension disc is loose, the loops are formed.	• Correct the tension disc.
• If thread is stuck in the tension disc.	• Remove the thread in the tension disc.

TDD_Final_Chapter08.indd 78 21-02-2019 11.40.54 AM