$$v \leq \sqrt{\mu_s rg}$$

$$\sqrt{\mu_s rg} = \sqrt{0.81 \times 10 \times 10} = 9 m s^{-1}$$

For Car C, $\sqrt{\mu_s rg}$ is less than v

The speed of car A, B and C are 7 m s^{-1}, 8 m s^{-1} and 10 m s^{-1} respectively. The cars A and B will have safe turns. But the car C has speed 10 m s^{-1} while it turns which exceeds the safe turning speed. Hence, the car C will skid.

3.7.3 Banking of Tracks

In a leveled circular road, skidding mainly depends on the coefficient of static friction μ_s The coefficient of static friction depends on the nature of the surface which has a maximum limiting value. To avoid this problem, usually the outer edge of the road is slightly raised compared to inner edge as shown in the Figure 3.44. This is called banking of roads or tracks. This introduces an inclination, and the angle is called banking angle.




Figure 3.44 Outer edge of the road is slightly raised to avoid skidding

Let the surface of the road make angle θ with horizontal surface. Then the normal force makes the same angle θ with the vertical. When the car takes a turn, there are two forces acting on the car:

a) Gravitational force mg (downwards)

b) Normal force N (perpendicular to surface)

We can resolve the normal force into two components. $N\cos\theta$ and $N\sin\theta$ as shown in Figure 3.46. The component $N\cos\theta$ balances the downward gravitational force 'mg' and component $N\sin\theta$ will provide the necessary centripetal acceleration. By using Newton second law

$$N\cos\theta = mg$$

$$N\sin\theta = \frac{mv^2}{r}$$

By dividing the equations we get $\tan\theta = \frac{v^2}{rg}$

$$v = \sqrt{rg\tan\theta}$$

The banking angle θ and radius of curvature of the road or track determines the safe speed of the car at the turning. If the speed of car exceeds this safe speed, then it starts to skid outward but frictional force comes into effect and provides an additional centripetal force to prevent the outward skidding. At the same time, if the speed of the car is little lesser than safe speed, it starts to skid inward and frictional force comes into effect, which reduces centripetal force to prevent inward skidding. However if the speed of the vehicle is sufficiently greater than the correct speed, then frictional force cannot stop the car from skidding.

UNIT-3(XI-Physics_Vol-1).indd 152 28-01-2020 13:48:54