

Figure 4.17 Perfect inelastic collision in one dimension

	Velocity		Linear momentum	
	Initial	Final	Initial	Final
Mass m_1	u_1	v	m_1u_1	m_1v
Mass m_2	u_2	v	m_2u_2	m_2v
	Total		$m_1u_1 + m_2u_2$	$(m_1+m_2)\,v$

The common velocity can be computed by

$$v = \frac{m_1u_1 + m_2u_2}{(m_1 + m_2)} \qquad (4.63)$$

EXAMPLE 4.21

A bullet of mass 50 g is fired from below into a suspended object of mass 450 g. The object rises through a height of 1.8 m with bullet remaining inside the object. Find the speed of the bullet. Take g = 10 ms^{-2}.

Solution

m_1 = 50 g = 0.05 kg; m_2 = 450 g = 0.45 kg



The speed of the bullet is u_1. The second body is at rest $(u_2 = 0)$. Let the common velocity of the bullet and the object after the bullet is embedded into the object is v.

$$v = \frac{m_1u_1 + m_2u_2}{(m_1 + m_2)}$$

$$v = \frac{0.05u_1 + (0.45\times 0)}{(0.05+0.45)} = \frac{0.05}{0.50}u_1$$

The combined velocity is the initial velocity for the vertical upward motion of the combined bullet and the object. From second equation of motion,

$$v = \sqrt{2gh}$$

$$v = \sqrt{2\times 10\times 1.8} = \sqrt{36}$$

$$v = 6\,ms^{-1}$$

Substituting this in the above equation, the value of u_1 is

$$6 = \frac{0.05}{0.50}u_1 \quad \text{or} \quad u_1 = \frac{0.50}{0.05}\times 6 = 10\times 6$$

$$u_1 = 60\,ms^{-1}$$

4.4.4 Loss of kinetic energy in perfect inelastic collision

In perfectly inelastic collision, the loss in kinetic energy during collision is transformed to another form of energy like sound, thermal, heat, light etc. Let KE_i be the total kinetic energy before collision and KE_f be the total kinetic energy after collision.

Total kinetic energy before collision,

UNIT-4(XI-Physics_Vol-1).indd 199 28-01-2020 13:52:11