The torque of the force $\vec{F}$ about O is, $\vec{\tau} = \vec{r} \times \vec{F}$. The component of the torque along the axis is the torque of $\vec{F}$ about the axis. To find it, we should first find the vector $\vec{\tau} = \vec{r} \times \vec{F}$ and then find the angle ϕ between τ and AB. (Remember here, $\vec{F}$ is not on the plane ABP). The torque about AB is the parallel component of the torque along AB, which is $|\vec{r} \times \vec{F}|$ cos ϕ. And the torque perpendicular to the axis AB is $|\vec{r} \times \vec{F}|$ sin ϕ.

The torque about the axis will rotate the object about it and the torque perpendicular to the axis will turn the axis of rotation. When both exist simultaneously on a rigid body, the body will have a *precession*. One can witness the precessional motion in a spinning top when it is about to come to rest as shown in Figure 5.9.




Figure 5.9 Precession of a spinning top

Study of precession is beyond the scope of the higher secondary physics course. Hence, it is assumed that there are constraints to cancel the effect of the perpendicular components of the torques, so that the fixed position of the axis is maintained. Therefore, perpendicular components of the torque need not be taken into account.

Hereafter, for the calculation of torques on rigid bodies we will:


1. *Consider only those forces that lie on planes perpendicular to the axis (and do not intersect the axis).*
2. *Consider position vectors which are perpendicular to the axis.*

Note

- Forces parallel to the axis will give torques perpendicular to the axis of rotation and need not be taken into account.
- Forces that intersect (pass through) the axis cannot produce torque as r = 0.
- Position vectors along the axis will result in torques perpendicular to the axis and need not be taken into account.

EXAMPLE 5.10

Three mutually perpendicular beams AB, OC, GH are fixed to form a structure which is fixed to the ground firmly as shown in the Figure. One string is tied to the point C and its free end D is pulled with a force F. Find the magnitude and direction of the torque produced by the force,



(i) about the points D, C, O and B

(ii) about the axes CD, OC, AB and GH.

UNIT-5(XI-Physics_Vol-1).indd 222 28-01-2020 13:55:45