(a) the *frequency* of the tuning fork or frequency of alternating current

(b) the *tension* in the string

(c) the unknown hanging *mass*

Construction:

The sonometer is made up of a hollow box which is one meter long with a uniform metallic thin string attached to it. One end of the string is connected to a hook and the other end is connected to a weight hanger through a pulley as shown in Figure 11.34. Since only one string is used, it is also known as monochord. The weights are added to the free end of the wire to increase the tension of the wire. Two adjustable wooden knives are put over the board, and their positions are adjusted to change the vibrating length of the stretched wire.

Working :

A transverse stationary or standing wave is produced and hence, at the knife edges P and Q, nodes are formed. In between the knife edges, anti-nodes are formed.

If the length of the vibrating element is l then

$$l = \frac{\lambda}{2} \Rightarrow \lambda = 2l$$

Let f be the frequency of the vibrating element, T the tension of in the string and μ the mass per unit length of the string. Then using equation (11.13), we get

$$f = \frac{v}{\lambda} = \frac{1}{2l}\sqrt{\frac{T}{\mu}} \text{ in Hertz} \qquad (11.66)$$

Let ρ be the density of the material of the string and d be the diameter of the string. Then the mass per unit length μ,

$$\mu = \text{Area} \times \text{density} = \pi r^2 \rho = \frac{\pi \rho d^2}{4}$$

$$\text{frequency } f = \frac{v}{\lambda} = \frac{1}{2l}\sqrt{\frac{T}{\frac{\pi d^2 \rho}{4}}}$$

$$\therefore \qquad f = \frac{1}{ld}\sqrt{\frac{T}{\pi\rho}} \qquad (11.67)$$

EXAMPLE 11.21

Let f be the fundamental frequency of the string. If the string is divided into three segments l_1, l_2 and l_3 such that the fundamental frequencies of each segments be f_1, f_2 and f_3, respectively. Show that

$$\frac{1}{f} = \frac{1}{f_1} + \frac{1}{f_2} + \frac{1}{f_3}$$

Solution

For a fixed tension T and mass density μ, frequency is inversely proportional to the string length i.e.

$$f \propto \frac{1}{l} \Rightarrow f = \frac{v}{2l} \Rightarrow l = \frac{v}{2f}$$

For the first length segment

$$f_1 = \frac{v}{2l_1} \Rightarrow l_1 = \frac{v}{2f_1}$$

For the second length segment

$$f_2 = \frac{v}{2l_2} \Rightarrow l_2 = \frac{v}{2f_2}$$

For the third length segment

$$f_3 = \frac{v}{2l_3} \Rightarrow l_3 = \frac{v}{2f_3}$$

Therefore, the total length

$$l = l_1 + l_2 + l_3$$

$$\frac{v}{2f} = \frac{v}{2f_1} + \frac{v}{2f_2} + \frac{v}{2f} \Rightarrow \frac{1}{f} = \frac{1}{f_1} + \frac{1}{f_2} + \frac{1}{f_3}$$

UNIT-11(XI-Physics_Vol-2)_14-08-2020.indd 257 17-08-2020 15:31:22