our naked eyes but it exists in the material itself. When a body is subjected to such a deforming force, internal force is developed in it, called as restoring force. The force per unit area is called as stress.

$$\text{Stress, } \sigma = \frac{\text{Force}}{\text{Area}} = \frac{F}{A} \qquad (7.1)$$

The SI unit of stress is N m^{-2} or pascal (Pa) and its dimension is [ML^{-1}T^{-2}]. Stress is a tensor.

(i) Longitudinal stress and shearing stress:

Let us consider a body as shown in Figure 7.3. When many forces act on the system (body), the center of mass (defined in unit 5) remains at rest. However, the body gets deformed due to these forces and so the internal forces appear. Let ΔA be the cross sectional area of the body. The parts of the body on two sides of ΔA exert internal forces $\vec{F}$ and $-\vec{F}$ on each other which is due to deformation. The force can be resolved in two components; F_n normal to the surface ΔA (perpendicular to the surface) and F_t tangential to the surface ΔA (tangent to the surface). The normal stress or longitudinal stress (σ_n) over the area is defined as

$$\sigma_n = \frac{F_n}{\Delta A}$$




Figure 7.3 Longitudinal stress

Similarly, the tangential stress or shearing stress σ_t over the area is defined as

$$\sigma_t = \frac{F_t}{\Delta A}$$

Longitudinal stress can be classified into two types, tensile stress and compressive stress.

Tensile stress

Internal forces on the two sides of ΔA may pull each other, i.e., it is stretched by equal and opposite forces. Then, the longitudinal stress is called tensile stress.




Figure 7.4 Tensile stress

Compressive stress

When forces acting on the two sides of ΔA push each other, ΔA is pushed by equal and opposite forces at the two ends. In this case, ΔA is said to be under compression. Then, the longitudinal stress is called compressive stress.




Figure 7.5 Compressive stress

UNIT-7(XI-Physics_Vol-2)_14-08-2020.indd 52 17-08-2020 11:30:47