Within the elastic limit, stress is proportional to strain (obey Hooke's law). Therefore, it shows a straight line behaviour. So, Young modulus can be computed by taking slope of these straight lines. Hence, calculating the slope for the straight line, we get

Slope of A > Slope of B > Slope of C

Which implies,

Young modulus of C < Young modulus of B < Young modulus of A

Notice that larger the slope, lesser the strain (fractional change in length). So, the material is much stiffer. Hence, the elasticity of wire A is greater than wire B which is greater than C. From this example, we have understood that Young's modulus measures the resistance of solid to a change in its length.

EXAMPLE 7.2

A wire 10 m long has a cross-sectional area 1.25×10^{-4} m^2. It is subjected to a load of 5 kg. If Young's modulus of the material is 4×10^{10} N m^{-2}, calculate the elongation produced in the wire. Take g = 10 ms^{-2}.

Solution

We know that $\frac{F}{A} = Y \times \frac{\Delta L}{L}$

$$\Delta L = \left(\frac{F}{A}\right)\left(\frac{L}{Y}\right)$$

$$= \left(\frac{50}{1.25\times10^{-4}}\right)\left(\frac{10}{4\times10^{10}}\right) = 10^{-4}\ \text{m}$$

Bulk modulus:

The bulk modulus is defined as the ratio of the volume stress to the volume strain.

Bulk modulus, K =

$$\frac{\text{Normal (Perpendicular) stress or Pressure}}{\text{Volume strain}}$$

The normal stress or pressure is

$$\sigma_n = \frac{F_n}{\Delta A} = \Delta p$$

The volume strain is

$$\varepsilon_v = \frac{\Delta V}{V}$$

Therefore, Bulk modulus is

$$K = -\frac{\sigma_n}{\varepsilon_v} = -\frac{\Delta P}{\frac{\Delta V}{V}} \qquad (7.7)$$

The negative sign in the equation (7.7) means that when pressure is applied on the body, its volume decreases. Further, the equation (7.7) implies that a material can be easily compressed if it has a small value of bulk modulus. In other words, bulk modulus measures the resistance of solids to change in their volume.

For an example, we know that gases can be easily compressed than solids. This means that gases have small value of bulk modulus compared to solids.


Compressibility

The reciprocal of the bulk modulus is called compressibility. It is defined as the fractional change in volume per unit increase in pressure.

From equation (7.7), we can say that the compressibility

$$C = \frac{1}{K} = -\frac{\varepsilon_v}{\sigma_n} = -\frac{\frac{\Delta V}{V}}{\Delta P} \qquad (7.8)$$

Since gases have small value of bulk modulus than solids, their values of compressibility is very high.



After pumping the air in the cycle tyre, usually we press the cycle tyre to check whether it has

UNIT-7(XI-Physics_Vol-2)_14-08-2020.indd 56 17-08-2020 11:30:51