Pressure energy per unit volume at A

$$\frac{\text{Pressure energy}}{\text{volume}} = \frac{P_A V}{V} = P_A$$

Pressure energy per unit mass at A

$$\frac{\text{Pressure energy}}{\text{mass}} = \frac{P_A V}{m} = \frac{P_A}{\frac{m}{V}} = \frac{P_A}{\rho}$$

Since m is the mass of the liquid entering at A in a given time, therefore, pressure energy of the liquid at A is

$$E_{PA} = P_A V = P_A V \times \left(\frac{m}{m}\right) = m\frac{P_A}{\rho}$$

Potential energy of the liquid at A,

$$PE_A = mg\,h_A,$$

Due to the flow of liquid, the kinetic energy of the liquid at A,

$$KE_A = \frac{1}{2} m\, v_A^2$$

Therefore, the total energy due to the flow of liquid at A, $E_A = E_{PA} + KE_A + PE_A$

$$E_A = m\frac{P_A}{\rho} + \frac{1}{2} mv_A^2 + mg\,h_A$$

Similarly, let a_B, v_B, and P_B be the area of cross section of the tube, velocity of the liquid, and pressure exerted by the liquid at *B*. Calculating the total energy at E_B, we get

$$E_B = m\frac{P_B}{\rho} + \frac{1}{2} mv_B^2 + mg\,h_B$$

From the law of conservation of energy,

$$E_A = E_B$$

$$m\frac{P_A}{\rho} + \frac{1}{2} mv_A^2 + mgh_A = m\frac{P_B}{\rho} + \frac{1}{2} mv_B^2 + mgh_B$$

$$\frac{P_A}{\rho} + \frac{1}{2} v_A^2 + gh_A = \frac{P_B}{\rho} + \frac{1}{2} v_B^2 + gh_B = \text{constant}$$

Thus, the above equation can be written as

$$\frac{P}{\rho g} + \frac{1}{2}\frac{v^2}{g} + h = \text{constant}$$

The above equation is the consequence of the conservation of energy which is true until there is no loss of energy due to friction. But in practice, some energy is lost due to friction. This arises due to the fact that in a fluid flow, the layers flowing with different velocities exert frictional forces on each other. This loss of energy is generally converted into heat energy. Therefore, Bernoulli's relation is strictly valid for fluids with zero viscosity or non-viscous liquids. Notice that when the liquid flows through a horizontal pipe, then $h = 0 \Rightarrow \frac{P}{\rho g} + \frac{1}{2}\frac{v^2}{g} =$ constant.

Applications of Bernoulli's Theorem

(a) Blowing off roofs during wind storm

In olden days, the roofs of the huts or houses were designed with a slope as shown in Figure.7.34. One important scientific reason is that as per the Bernoulli's principle, it will be safeguarded except roof during storm or cyclone.




Figure 7.34 Roofs of the huts or houses

During cyclonic condition, the roof is blown off without damaging the other parts of the house. In accordance with the Bernoulli's principle, the high wind blowing over the roof creates a low-pressure P_1. The pressure under the roof P_2 is greater. Therefore, this pressure difference $(P_2 - P_1)$ creates an up thrust and the roof is blown off.

UNIT-7(XI-Physics_Vol-2)_14-08-2020.indd 84 17-08-2020 11:31:25