From the above equation, the pressure difference

$$\Delta P = P_1 - P_2 = \rho \frac{v_1^2}{2} \frac{(A^2 - a^2)}{a^2}$$

Thus, the speed of flow of fluid at the wide end of the tube A

$$v_1^2 = \frac{2(\Delta P)a^2}{\rho(A^2 - a^2)} \Rightarrow v_1 = \sqrt{\frac{2(\Delta P)a^2}{\rho(A^2 - a^2)}}$$

The volume of the liquid flowing out per second is

$$V = Av_1 = A\sqrt{\frac{2(\Delta P)a^2}{\rho(A^2 - a^2)}} = aA\sqrt{\frac{2(\Delta P)}{\rho(A^2 - a^2)}}$$

**(e) Other applications**

This Bernoulli's concept is mainly used in the design of carburetor of automobiles, filter pumps, atomizers, and sprayers. For example, the carburetor has a very fine channel called nozzle through which the air is allowed to flow in larger speed. In this case, the pressure is lowered at the narrow neck and in turn, the required fuel or petrol is sucked into the chamber so as to provide the correct mixture of air and fuel necessary for ignition process.

**Activity**

A bottle is filled with thermocol balls. One end of a flexible tube is kept inside the bottle immersed inside the balls. The free end is rotated and we find the balls sprayed all around. This explains the working of an atomizer or sprayer.




A spider web is much stronger than what we think. A single strand of spider silk can stop flying insects which are tens and thousands times its mass. The young's modulus of the spider web is approximately $4.5 \times 10^9\, N\, m^{-2}$. Compare this value with Young's modulus of wood.





UNIT-7(XI-Physics_Vol-2)_14-08-2020.indd 86 17-08-2020 11:31:27